



Wall Covering: Arouca Beige, Skins Empyreal Moon Light Floor Covering: Linkfloor Eco Dynasty Brown

LIMESTONE / CALIZA / PIERRE CALCAIRE



AROUCA BEIGE



Europe



Indoor Wall Covering



Outdoor Wall Covering



Moderate Color Variation



Matt




Irregular Texture

DESCRIPTION	FORMAT	CODES	GROUP	PCS	M ²	KG
Arouca Beige	15/20cm x 25-50cm x 2,5-3cm 5 7/8" / 7 7/8" x 9 7/8-19 5/8" x 1"-1 1/8"	100355052	G-260	1 x Cj 72 x Pal	0,28 x Cj 20,16 x Pal	17,6 x Cj 1267,2 x Pal

Widths of 15cm and 20cm. Free lengths from 25cm to 50cm. Thicknesses vary from 2,5cm to ± 3cm. Minimum recommended joint of 2 - 3 mm. It is advisable to waterproof the material after installation and before grouting.

Anchos de 15cm y 20cm. Largos libres desde 25cm hasta 50cm. Espesores variables de 2,5cm a ± 3cm. Junta mínima recomendada de 2 - 3 mm. Se aconseja hidrofugar el material tras la instalación y antes de rejuntar.

Largeurs de 15cm et 20cm. Longueurs libres de 25cm à 50cm. Les épaisseurs varient de 2,5 cm à ± 3 cm. Joint minimum recommandé de 2 à 3 mm. Il est conseillé d'imperméabiliser le matériau après l'installation et avant le jointoiment.



Recommended Joint:
COLORSTUK RAPID BEIGE N

Recommended Adhesive:
SUPER-ONE N BLANCO

Special corner pieces possible
Posibilidad de piezas especiales para esquina
Possibilité de pièces d'angle spéciales



AROUCA GREY



Europe



Indoor Wall Covering



Outdoor Wall Covering



Strong Color Variation



Matt




Irregular Texture

DESCRIPTION	FORMAT	CODES	GROUP	PCS	M ²	KG
Arouca Grey	15/20cm x 25-50cm x 2,5-3cm 5 7/8" / 7 7/8" x 9 7/8-19 5/8" x 1"-1 1/8"	100355053	G-260	1 x Cj 90 x Pal	0,28 x Cj 25,2 x Pal	12,78 x Cj 1150 x Pal

Widths of 15cm and 20cm. Free lengths from 25cm to 50cm. Thicknesses vary from 2,5cm to ± 3cm. Minimum recommended joint of 2 - 3 mm. It is advisable to waterproof the material after installation and before grouting.

Anchos de 15cm y 20cm. Largos libres desde 25cm hasta 50cm. Espesores variables de 2,5cm a ± 3cm. Junta mínima recomendada de 2 - 3 mm. Se aconseja hidrofugar el material tras la instalación y antes de rejuntar.

Largeurs de 15cm et 20cm. Longueurs libres de 25cm à 50cm. Les épaisseurs varient de 2,5 cm à ± 3 cm. Joint minimum recommandé de 2 à 3 mm. Il est conseillé d'imperméabiliser le matériau après l'installation et avant le jointoiment.



Recommended Joint:
COLORSTUK RAPID MANHATTAN N

Recommended Adhesive:
SUPER-ONE N BLANCO

Special corner pieces possible
Posibilidad de piezas especiales para esquina
Possibilité de pièces d'angle spéciales